



LIQUID LEAK DETECTION SYSTEMS

FG-NET

Digital Unit for Leak Detection and Location

Product Datasheet



- ▶ Digital, Fully Addressable
- ▶ Monitoring Up to 500 Sense Cables
- ▶ Touch Screen Interface
- ▶ Instant Locating of Faults
- ▶ Integrated Monitoring Software
- ▶ TCP/IP & MODBUS/JBUS Connection

Description

The FG-NET digital unit is designed to be used with all TTK digital sense cables, for water, bases, acid and hydrocarbon leak detection.

In the event of a fault on the sense cables (leak or cable break):

Primary responses from the FG-NET:

- An audible alarm is triggered and a relay is activated.
- The touch screen of the panel displays the location of the leak and details of the fault (the type of fault leak or cable break), including the time and date the fault is registered.
- Optional – integrated maps of the leak detection installation highlighting the location of the fault, available on the touch screen display of FG-NET.

Secondary advanced responses :

- Report to the BMS via a JBUS/MODBUS protocol. The FG-NET can drive dynamic drawings on the host BMS.
- Send email alerts and SNMP traps to a LAN-connected BMS, via a standard Ethernet connection.

Features & Benefits

FEATURES

- 7" (175mm) touch-screen gives a clear and detailed indication of the system status.
- User-friendly system - Users can customise the system with the sub menus accessible from the home screen, to set up the panel.
- Up to 120 lengths of sense cables (or 1800 metres) can be managed independently.
- The system's reaction time to faults is adjustable cable by cable.
- Temporal isolation (72 hours maximum) a or several sense cables.
- Up to 5000 events stored in the history log.
- Non-volatile memory (SD), for storing user settings and drawings.
- Three types of interface for communication with a BMS available.
 - TCP/IP connection via an Ethernet port.
 - JBUS/MODBUS RS232 or RS422/485 serial links.
 - 9 relay contacts: 8 configurable relays + 1 specific relay for power interruption.
 - Dual relay drive (e.g. 1 for BMS and 1 for solenoid valve);
 - Relay positions are defined by a LED indicator.
- Different security levels to provide maximum security.

BENEFITS

- Precise location of a leak: to the nearest metre for water and acid leak detection and to the section for oil leak detection.
- Each sense cable is addressable and can be assigned a specific name.
- Multiple simultaneous leaks can be detected (120 cables = 120 alarms).
- Different types of sense cables (for detecting conductive & non-conductive liquids) can be connected on the same panel for a truly bespoke system.
- Cable break faults can be detected (to the nearest cable).
- When a cable break occurs, the system maintains its integrity by continuing to monitor all preceding cables for faults.
- Compatible with existing monitoring systems (Trend BMS etc.)
- Extension and upgrade of the system is easy. No additional power source or zoning panels are required.

Touch Screen Menus


Four menus available for configuration of the FG-NET :

| | |
|------------------|--|
| Setup | Main page for setting up the system architecture, cable isolation and reaction time rules, acknowledge mode, user access, relay status, time zone, language, sound alarm, serial links and network functionalities. An administrator level password is required to access this menu. |
| Event log | For viewing the recorded alarm history. A maximum of 5000 events can be stored in the event log. |
| Cables | To give the user a general overview of the site installation. The interactive floor plan can be viewed under this menu as an optional feature. |
| Help | Provides troubleshooting procedures, contact details of the manufacturer and the reference number of the unit. |


Screen Shots



Simultaneous alarms displayed on one screen



Dynamic map shows leak in real time



Easy setup of relays for each cable



User-friendly interface of configuration

Technical Data

| | |
|---|--|
| Compatibility | Sense cables (digital): FG-EC, FG-AC, FG-OD range of cables Sense cables (analog through FG-DTCS box): FG-ECS, FG-ACS Satellite devices: FG-BBOX, FG-RELAYS Diversion boxes: FG-DTC, FG-DTCS, FG-DCTL, FG-DOD Accessories: TTK 8723, 8771 jumper cable, FG-CLC, FG-TMC |
| Dimensions & Weights | Wall mounted W: 228 mm H: 303 mm D: 67 mm Weight: 2.3kg Rack mounted W: 483 mm H: 177 mm D: 74 mm Weight: 3kg |
| Maximum Length of Sense Cable | 500 sense cables (500 x 15m=7500m) when use with FG-BBOX |
| Accuracy | water & acid leak detection: +/- 1 meter ; oil leak detection: section |
| Operating Languages | English, French, German |
| Voltage Input | 100 to 240 VAC, 50-60 Hz |
| Power Consumption | 36VA Max |
| Working Temperature Range | 5°C to 55°C |
| Working Humidity Range | 5% to 80% non-condensing |
| Relay Types | Volt free dry contact (NO, NC, COM) |
| Relay Numbers | 9 (8 + 1 power failure relay) |
| Serial Connection | MODBUS/JBUS RS232 or RS422/485 |
| Maximum Relay Switching Voltage | 125 V AC and 220 V DC |
| Maximum Relay Switching Capacity | 60 W (30 V x 2A) |
| Ingress Protection | IP40 - Indoor use only |

Identification Codes

| | |
|----------------------------|---|
| FG-NET (F / E) | Digital Touchscreen Leak Detection Panel (Wall Mounted / Rack Mounted) |
| FG-BBOX F | FG-NET's Satellite Device - 2 Circuits Black Box (Wall Mounted) |
| FG-RELAYS F | FG-NET's Satellite Device - 24 x External Relays (Wall Mounted) |
| FG-EC, FG-AC, FG-OD | Addressable Water, Acid, Hydrocarbon Sensing Cable With Connectors |
| Accessory Boxes: | |
| FG-DTC | Diversion Box for 'TTK Bus 8723' |
| FG-DTCS | Addressable Box for one Water or Acids Cable, on 'TTK Bus 8723' (Sector Mode) |
| FG-DCTL | 'Cut-To-Length' Addressable Box for one Water or Acids Cable, on 'TTK Bus 8723' (Sector Mode) |
| FG-DOD | Bus Interface, for Integration of FG-OD Cables |

Certificates



FG-NET digital unit meets the TÜV requirements.
FG-OD sense cables which are certified by ATEX can be connected to the FG-NET digital unit.

All the connections in the FG-NET digital unit must be done with the power supply switched off.
Read carefully the installation procedure for the FG-NET digital unit.

This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this product. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use.
FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2020

- **TTK Headquarters** / 19, rue du Général Foy / 75008 Paris / France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / www.ttk.fr / ventes@ttk.fr
- **TTK UK Ltd.** / 3 Luke Street / London EC2A 4PX / United Kingdom / T : +44 207 729 6002 / F : +44 207 729 6003 / www.ttkuk.com / sales@ttkuk.com
- **TTK Pte Ltd.** / #09-05, Shenton House, 3 Shenton Way / Singapore 068805 / T: +65.6220.2068 / M: +65.9271.6191 / F: +65-6220.2026 / www.ttk.sg / sales@ttk.sg
- **TTK Asia Ltd.** / 2107-2108 Kai Tak Commercial Building / 317 Des Voeux Road Central / Hongkong / T: +852.2858.7128 / F: +852.2858.8428 / www.ttkasia.com / info@ttkasia.com
- **TTK Middle East FZCO** / Building 6EA, Office 510 PO Box 54925 / Dubai Airport Free Zone / UAE / T: +971 4 70 17 553 / M: +971 50 259 66 29 / www.ttkuk.com / cgalmiche@ttk.fr
- **TTK Deutschland GmbH** / Berner Strasse 34 / 60437 Frankfurt / Deutschland / T : +49(0)69-95005630 / F : +49(0)69-95005640 / www.ttk-gmbh.de / vertrieb@ttk-gmbh.de
- **TTK North America Inc** / 1730 St Laurent Boulevard Suite 800 / Ottawa, ON, K1G 5L1 / Canada / T : +1 613 566 5968 / www.ttkcanada.com / info@ttkcanada.com
- **Thomas Sales & Marketing Inc. TTK Master Distributor For USA** / 7200 W 66th St / Bedford Park, IL 60638 / The United States / T: +1 630-518-4724 / www.ttkusa.com / dmolk@ttkusa.com